

Fujitsu recommends Windows.

Data Sheet

FUJITSU ESPRIMO E420 E85+ Desktop PC

Your Immediately Deliverable Office PC

The FUJITSU ESPRIMO E420 delivers high-quality computing for your office applications and projects at a very attractive price point. You can choose cost-optimized fixed configurations for immediate delivery. Alternatively, you can use configuration options to meet your specific hardware needs, while staying within your budget.

High performance and best price/performance ratio

Cost-effective small form factor desktop for price-conscious customers

- 4th generation Intel® Core™ processor family

Flexibility

Freedom of choice with tailored systems, perfect fit for specific requirements

- Flexible logistic concept - optional customizing program

Reliability

High-quality and functional stability

- Development and production in Europe

Lifecycle

Hardware continuity for long-term projects

- Managed lifecycle up to 12 months

Meets ENERGY STAR® requirements

Low power consumption and low costs, without any loss in performance

- Power supply with 85% efficiency



Components

Processor	Intel® Core™ i7-4790 processor (4 Cores / 8 Threads, 3.60 GHz, up to 4.0 GHz, 8 MB, Intel® HD Graphics 4600) *
	Intel® Core™ i5-4690 processor (4 Cores / 4 Threads, 3.50 GHz, up to 3.9 GHz, 6 MB, Intel® HD Graphics 4600) *
	Intel® Core™ i5-4590 processor (4 Cores / 4 Threads, 3.30 GHz, up to 3.7 GHz, 6 MB, Intel® HD Graphics 4600) *
	Intel® Core™ i5-4460 processor (4 Cores / 4 Threads, 3.20 GHz, up to 3.4 GHz, 6 MB, Intel® HD Graphics 4600)
	Intel® Core™ i5-4440 processor (4 Cores / 4 Threads, 3.10 GHz, up to 3.3 GHz, 6 MB, Intel® HD Graphics 4600)
	Intel® Core™ i3-4160 processor (2 Cores / 4 Threads, 3.60 GHz, 3 MB, Intel® HD Graphics 4400)
	Intel® Pentium® processor G3450 (2 Cores / 2 Threads, 3.40 GHz, 3 MB, Intel® HD Graphics)
	Intel® Pentium® processor G3250 (2 Cores / 2 Threads, 3.20 GHz, 3 MB, Intel® HD Graphics)
	Intel® Celeron® processor G1840 (2 Cores / 2 Threads, 2.80 GHz, 2 MB, Intel® HD Graphics)
	*with Intel® Turbo Boost Technology (clock speed and performance will vary depending on workload and other variables)
Operating systems	
Operating system	Windows 8.1 Pro
	Windows 8.1
	Windows 7 Professional 64-bit
	Windows 7 Professional 32-bit
Operating system compatible	openSUSE Linux
Memory modules	2 GB (1 module(s) 2 GB) DDR3, unbuffered, non-ECC, 1,600 MHz, PC3-12800, DIMM
	4 GB (1 module(s) 4 GB) DDR3, unbuffered, non-ECC, 1,600 MHz, PC3-12800, DIMM
	8 GB (1 module(s) 8 GB) DDR3, unbuffered, non-ECC, 1,600 MHz, PC3-12800, DIMM
Hard disk notes	Up to 20 GB of HDD space is reserved for system recovery
	SSHD (Solid State Hard Disk, Hybrid drive)
	SSD (Solid State Disk)
	SED (Self-Encrypting Drive)
Hard disk drives (internal)	SSHD SATA III, 7,200 rpm, 1,000 GB, 3.5-inch
	SSHD SATA III, 5,400 rpm, 500 GB, 2.5-inch
	SSD SATA III Premium, 512 GB, 2.5-inch
	SSD SATA III, 256 GB, 2.5-inch, SED
	SSD SATA III, 256 GB, 2.5-inch
	SSD SATA III, 128 GB, 2.5-inch, SED
	SSD SATA III, 128 GB, 2.5-inch
	HDD SATA III, 7,200 rpm, 2,000 GB, 3.5-inch
	HDD SATA III, 7,200 rpm, 1,000 GB, 3.5-inch
	HDD SATA III, 7,200 rpm, 500 GB, 3.5-inch
	HDD SATA III, 7,200 rpm, 250 GB, 3.5-inch
	HDD SATA II, 5,400 rpm, 320 GB, 2.5-inch
Graphics	NVIDIA® GeForce® GTX 745 2 GB LP, 2 GB
	NVIDIA® GeForce® GT630 DisplayPort 2GB LP, 2 GB
	NVIDIA® GeForce® 605 DisplayPort 1GB LP, 1 GB
	DVI to VGA Adapter
	DP to DVI-D (single link) Adapter Cable
Drives (optional)	BD Triple Writer SATA slim (tray)
	DVD-ROM
	DVD Super Multi
	MultiCard Reader 24in1 USB 2.0 3.5"

**Interface add on cards/components
(optional)**

WLAN 802.11 a/g/n (2x2), (dedicated regions only, not for Indonesia)
 USB 3.0 PCIe x1
 Gigabit Ethernet PCIe x1, DS
 Dual serial card PCIe x1

Base unit

Base unit	ESPRIMO E420 E85+
Mainboard	
Mainboard type	D3230
Formfactor	µATX
Chipset	Intel® H81
Processor socket	LGA 1150
Processor quantity maximum	1
Memory slots	2 DIMM (DDR3)
Supported capacity RAM (max.)	16 GB
Memory frequency	1,600 MHz
Memory notes	Dual channel support. For dual channel performance, identical memory modules in each channel are necessary (minimum 2 modules).
LAN	10/100/1,000 MBit/s Realtek RTL8111G
BIOS version	AMI Aptio 4.6
BIOS features	BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI)
Audio type	On board
Audio codec	Realtek ALC671
Audio features	High Definition Audio, 5.1 surround sound
I/O controller on board	
Serial ATA total	3
thereof SATA III	2
Controller functions	Serial ATA II (3 Gbit) Serial ATA III (6 Gbit) NCQ AHCI
Interfaces	
Audio: line-in	1
Audio: line-in / microphone	1
Audio: line-out	1
Front audio: microphone	1
Front audio: headphone	1
USB 2.0 total	6
USB 3.0 total	2
USB front	2x 2.0
USB rear	2x 2.0/ 2x 3.0
USB internal	2x 2.0
VGA	1
DVI	1 (DVI-D)
Mouse / Keyboard (PS/2)	1/1
Ethernet (RJ-45)	1

Input device / components

	Optical USB wheel mouse
Input devices (optional)	Optical USB/PS2 tilt wheel mouse KBPC PX ECO Mouse M440 ECO

Drive bays

Drive bays total	3
3.5-inch internal bays	1
3.5-inch external bays	1
5.25-inch external bays	1
Drive bay notes	3,5" bay can be used for 2,5" drives; optional external bay as internal 3,5";

Slots

PCI-Express 2.0 x16	1 x (210 mm / 8.27 inch) Low profile
PCI-Express x1	2 x (210 mm / 8.27 inch) Low profile

Graphics on board

Graphics brand name	Intel® HD Graphics, HD Graphics 4400, HD Graphics 4600 (depending on processor)
Shared video memory	up to 1,782 MB
TFT resolution (VGA)	1,024 x 768 pixel 1,280 x 1,024 pixel 1,360 x 768 pixel 1,440 x 900 pixel 1,600 x 900 pixel 1,600 x 1,200 pixel 1,680 x 1,050 pixel 1,920 x 1,080 pixel
TFT resolution (DVI)	1,280 x 1,024 pixel 1,360 x 768 pixel 1,440 x 900 pixel 1,600 x 900 pixel 1,680 x 1,050 pixel 1,920 x 1,080 pixel 1,920 x 1,200 pixel
Graphics features	Dual display support DirectX® 11.1 HDCP support Open CL® 1.2 OpenGL® 4.0
Graphics notes	up to 1 GB dedicated video memory (main memory owned and locked for graphics use) Tested resolutions, depending on display type additional resolutions and frequencies possible Shared memory depending on main memory size and operating system Resolution (color depth up to 32 Bit/pixel) For TFT we recommend using 60Hz

Electrical values

Power efficiency note	power supply efficiency (at 230V; 20% / 50% / 100% load) : 83% / 86% / 85% 0-Watt mode with hard-off switch
Rated voltage range	100 V - 240 V
Rated frequency range	50 Hz - 60 Hz
Operating voltage range	90 V - 264 V
Operating line frequency range	47 Hz - 63 Hz
Max. output of single power supply	280 W
Power factor correction/active power	active
Monitor outlet	No

Power consumption

Power consumption note	See white paper Energy Consumption 0-Watt mode with hard-off switch
Link to Energy White Paper	http://docs.ts.fujitsu.com/dl.aspx?id=2c6e5b60-abb9-4d9e-9d04-d9a07e83eeac

Heat dissipation

Heat dissipation notes	See white paper Energy Consumption
------------------------	------------------------------------

Noise emission

Related Processors for noise	Intel® Core™ i7 4770
Standard noise emission	2x2 GB, HDD, ODD, Windows According to ISO 7779:2010, ECMA-74
Standard noise notes / description	A-weighted sound power level L _{wad} (in B) / Workplace related A-weighted sound pressure level L _{pAm} (in dB(A)) Bystander position
Standard noise operation mode: CPU 50% load	3.6 B / 22 dB(A) Bystander; 25 dB(A) Operator position
Standard noise operation mode: HDD load	3.4 B / 21 dB(A) Bystander; 23 dB(A) Operator position
Standard noise operation mode: Idle mode	3.3 B / 20 dB(A) Bystander; 22 dB(A) Operator position
Standard noise operation mode: ODD load	4.6 B / 31 dB(A) Bystander; 36 dB(A) Operator position
Standard noise operation mode: Office applications 2.0	3.3 B / 20 dB(A) Bystander; 22 dB(A) Operator position

Dimensions / Weight / Environmental

Dimensions (W x D x H)	330 x 405 x 104 mm 13.0 x 15.95 x 4.1 inch
Operating position	horizontal / vertical (optional, feet needed)
Weight	9 kg
Weight (lbs)	20.22 lbs
Weight notes	Actual weight may vary depending on configuration
Operating ambient temperature	10 - 35 °C (50 - 95 °F)
Operating relative humidity	5 - 85 % (relative humidity)

Compliance

Product	ESPRIMO E420
Model	DTL2
Germany	TÜV GS
Europe	CE
USA/Canada	FCC Class B cCSAus
Global	RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL) EPEAT® Gold (dedicated regions) ENERGY STAR® 6.0 (dedicated regions)
Compliance link	http://globalsp.ts.fujitsu.com/sites/certificates

Additional Software

Additional software (preinstalled)	Workplace Protect (secure authentication solution) Adobe® Reader® (pdf reader) McAfee Multi Access Security (anti-virus and internet security software; 60 days trial version) Win7: Fujitsu Recovery (hard disk based recovery) Win8: Microsoft Push Button Recovery (hard disk based recovery) Microsoft Office (buy license to activate the pre-installed Microsoft Office)
Additional software (optional)	Recovery DVD for Windows® Drivers & Utilities DVD (DUDVD) CyberLink PowerDVD BD (playback software for Blu-ray Disc™) CyberLink PowerDVD DVD (playback software for DVD) Nero Essentials XL

Manageability

Manageability technology	DeskUpdate Driver management PXE 2.1 Boot code Wake up from S5 (off mode) WoL (Wake on LAN)
--------------------------	--

Supported standards	DMI PXE WMI
---------------------	-------------------

Security

Physical Security	Kensington Lock support Eye for padlock
-------------------	--

System and BIOS Security	Boot sector virus protection Write protect option for the Flash EPROM Control of external interfaces
--------------------------	--

User Security	User and supervisor BIOS password Hard disk password Access protection via external SmartCard reader (optional) Access protection via internal SmartCard reader (optional)
---------------	---

Miscellaneous**Packaging information**

Packaging dimension (mm)	467 x 265 x 540 mm
Packaging dimension (inch)	18.39 x 10.43 x 21.26 inch
Max. quantity / pallet	28
Material - Weight (g) Carton	1140 g
Material - Weight (lbs) Carton	2.51 lbs
Material - Weight (g) EPS / PS	180 g
Material - Weight (lbs) EPS / PS	0.4 lbs
Material - Weight (g) PE	60 g
Material - Weight (lbs) PE	0.13 lbs
Packaging notes	printed user documentation is bleached in chlorine free process

Warranty

Standard Warranty	1 year
Service level	Bring-In / Onsite Service (for countries within region FTS CEMEA&I, for all other countries depending on local regulations, minimum: 1 year material warranty)
Warranty Terms & Conditions	http://support.ts.fujitsu.com/warranty

Product Support Services - the perfect extension

Recommended Service	9x5, Response Time: Next Business Day
Spare Parts availability	5 years after end of product life
Service Weblink	http://www.fujitsu.com/fts/services/support

Recommended Accessories

Display E19-7 LED	The FUJITSU Display E19-7 LED combines comfortable ergonomics with best-in-class energy saving technology like ECO operation mode.	Order Code: S26361-K1482-V160
Display B24W-7 LED	The FUJITSU B24W-7 LED Display with excellent ergonomics makes intensive office work extremely comfortable. This highly reliable display offers superb usability and power-saving features to help reduce your labor as well as energy costs. With wide viewing angle technology, flexible connectivity, and easy manageability, the FUJITSU B24W-7 LED Display can help you improve productivity.	Order Code: S26361-K1497-V140

Mouse M440 ECO

Fujitsu Mouse M440 ECO is made from 100% bio material and has a completely PVC free cable. The elegant M440 ECO works on nearly every surface and follows all your hand movements smoothly and precisely. It features two main buttons and as well as a scroll wheel providing comfortable computing to both right and left-handed users.

Order Code:
S26381-K450-L200

SOUNDSYSTEM DS E2000 Air

The new more powerful SOUNDSYSTEM DS E2000 Air gives you impressive, well-balanced sound throughout the frequency band. It is an unbeatable USB speaker set with a surprisingly small form factor. The robust satellite speakers are decorated with a deluxe piano finish and the base is adorned with warm ambient lighting.

Order Code:
S26391-F7128-L600

UC&C USB Headset Stereo H650e

The UC&C USB Headset Stereo H650e is the ultimate in style and functionality. Long, uncomfortable work calls are a thing of the past thanks to the cushioned ear pads and crystal clear sound. Adjustable headband and microphone provides the perfect fit for everyone. Optimized for Microsoft® Lync™ the headset displays a red 'in-call' LED to let your co-workers know when you're available, thus helping to boost office productivity.

Order Code:
S26391-F7139-L10

Busylight UC Lync

Boost communication and productivity in the office with the Busylight. The genius of this device is that it both advertises your present working state and promotes the use of Lync, making your office more efficient. Perfect for the work environment in open-plan offices, the Busylight makes users feel comfortable with Lync's features and eases the transition from traditional office internal telephone systems.

Order Code:
S26391-F7139-L30

HS E2000 Communicator Headset

The Fujitsu HS E2000 Communicator headset allows you to use your personal computer for Voice over IP (VoIP) in stereo audio quality. This premium headset is designed to provide superb audio quality and comfort for the telephony, internet chat, speech recognition, video conferencing and multimedia applications.

Order Code:
S26391-F7139-L5

Keyboard KBPC PX ECO

Fujitsu's KBPC PX ECO keyboard is the perfect contribution to Green IT. The keyboard is made out of 45% renewable raw material and comes with a PVC free USB cable. In addition, the KBPC PX ECO offers first class comfort and ergonomics. It attracts attention with its impressive modern design and useful extras.

S26381-K341-L1** (**: country specific variation)

More information

Fujitsu OPTIMIZATION Services

In addition to FUJITSU ESPRIMO E420 E85+, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/services/computing/

Software

www.fujitsu.com/software/

More information

Learn more about FUJITSU ESPRIMO E420 E85+, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
www.fujitsu.com/fts/ESPRIMO

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see www.fujitsu.com/terms
Copyright © Fujitsu Technology Solutions

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

Fujitsu Technology Solutions
Website: www.fujitsu.com/fts
2014-12-16 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see www.fujitsu.com/terms
Copyright © Fujitsu Technology Solutions